

# GRADA PVA ULTRA

## PVC - VINYL AND CARPET COATING ADHESIVE

### DEFINITION

It used for adhering PVC rolls and tiles to the floor  
It is a strong, water-based, solvent-free, acrylic-based adhesive.

### USAGE AREAS

It is used in the assembly of PVC, polyurethane and latex-based floor coverings.

Used in hospitals, showroom, store and other optional floors

### FEATURES

It is durable for winter conditions. It provides an excellent adhesion.

Suitable for underfloor heated floors.

Color	Off-white
Specific Gravity	1,2 gr/ cm <sup>3</sup>
p H	7
Crust making time	2 hours
Assembly Time	45 minutes

### APPLICATION

The surface on which PVC, vinyl or other coating materials will be applied must be smooth, clean, dry and free of cracks. In case the surface is not smooth or there is deformation, the surface should be smoothed with floor leveling screed. GRADA PVA ULTRA is spread on the floor with an A2, A3 or B1 comb. PVC, vinyl or other covering material is installed 10-20 minutes after the material is spread on the floor. During the application, the ambient temperature should not be below + 5°C. Hot welding should be done after 24 hours. At the end of the work, cleaning can be done with warm water. Cleaning of the tools used is also done with warm water.

### CONSUMPTION

0,250-0,300 kg/m<sup>2</sup>

### PACKAGING

A component: 8,60 kg  
(6.00L)

B component : 1,40 kg  
(1.00L)

### SHELF LIFE

1 year from the date of production, under suitable storage conditions (in a cool and dry environment at +5°C – +35°C).

### SAFETY PRECAUTIONS

During the application, work clothes, protective gloves and glasses in accordance with the occupational and worker health rules should be used. Due to their irritating effects, the components should not come into contact with the skin and eyes. In case of contact, they should be washed with plenty of soap and water. If swallowed, a doctor should be consulted immediately. Application areas should be ventilated and food and beverage materials should not be brought into the application areas. It should be stored out of the reach of children. For detailed information, see the Material Safety Data Sheet.

### LIABILITY

The data contained in this technical document is based on our scientific and practical knowledge. Grada Construction Chemicals Industry. ve Tic. Inc. only responsible for the quality of the product. Apart from the written suggestions about where and how the product will be used, and/or the consequences that may occur due to incorrect use, Grada Yapı Chemicals San. ve Tic. A.Ş. cannot be held responsible. The responsibility for the correct application of our product rests with the user.



**GRADA YAPI KİMYASALLARI VE İNŞAAT MALZEMELERİ ÜRETİM SAN. TİC. A.Ş.**

Adres : Çınardere Mah.Akan Sokak No:13 Kat.2 3 Nolu Bölüm Pendik -İstanbul /TÜRKİYE

Telefon : +90 216 379 83 53 -52 Fax : +90 216 379 83 51

E-mail : info@grada.com.tr web : www.grada.com.tr