

GRADABRUT 110 PRIMER

Technical Data Sheet Date: 14.07.2020

Description

Acrylic emulsion based adherence primer.

Application Areas

- Cementitious Stucco
- Smooth Concrete
- Smooth surfaces
- Gas concrete

Feature and Benefits

Applied as a primer on high porosity and absorptivity exterior walls of buildings that the purpose of increasing adherence and reducing consumption of final layer paint and coating.

Technical Information

Content	Acrylic
Color	Blue
Appearance	Viscous
Particle Size	Liquid Class
Solid Conten	S1
Mixing Ratio	25±2 % Water
Recommended	0,150 – 0,300 kg/ m ²
Coat Application	1 coat
Tools Drying Time	Roller / Brush
	2 hours to touch
	12 hours to topcoat

Application

Primer is diluted with water in the ratio of %25 and mixed until it reaches a homogenous state. Primer should be applied as one layer with lambskin roller or brush. Paint or coating application should be started at least 12 hours later, after the application of primer. During application the



GRADABRUT 110 PRIMER

surface and ambient temperature should be between +5°C and +30°C and protect the surface from frost.

Packaging

12kg plastic bucket

Shelf Life

12 months in original, unopened package

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below 0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.

Health and Safety

Warning! Cause eye and skin irritation. If eye contact, flush eyes with water for several minutes and remove contacts if present and easy to do. Get immediate medical attention. If skin contact; wash skin with plenty of soap and water. Get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.



GRADABRUT 110 PRIMER

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from GRADA A.Ş. Please contact with technical service department for further information and support.